## Myrtle Beach Harley-Davidson Service Department Vehicle Maintenance Schedule

## **DYNAS**

		1,000	2,500			
Item Serviced	Procedure	5,000	7,500	10,000	20,000	30,000
Engine Oil & Filter	Replace or Inspect Level	R	Ī	R	R	R
Oil Lines & Brake Lines	Inspect for leaks	ı				I
Air Cleaner	Inspect and Clean	I/C	I/C	I/C	I/C	I/C
Tires	Inspect Tread, Check Pressure	I/C	I/C	I/C	I/C	I/C
Wheel Spokes	Check Tightness	С		С	С	С
Primary Chaincase Fluid	Replace or Inspect Level	R		R	R	R
Primary Chain	Adjust	Α	Α	Α	Α	Α
Transmission fluid	Replace or Inspect Level	R		R	R	R
Clutch	Adjust	Α		Α	Α	Α
Clutch Cable	Adjust and Lubricate	A/L		A/L	A/L	A/L
Rear Belt and Sprockets	Inspect, Adjust Belt	I/A	I/A	I/A	I/A	I/A
Throttle and Enrichner Cables	Adjust and Lubricate	A/L		A/L	A/L	A/L
Clutch and Brake Levers	Lubricate	L	Ц	L	L	┙
Kick Stand	Adjust and lubricate	A/L		A/L	A/L	A/L
Fuel Valve, Lines and Fittings	Inspect for Leaks	I				
Fuel Tank Filter Screen	Clean or Replace				C/R	
Brake Fluids	Check Levels and Condition	С		С	С	С
Brake Pads and Discs	Inspect for Wear	I				ı
Brake Components: Caliper						
Pins, Boots, Bushings	Inspect or Lubricate	I	1	1	L	L
Shifter Linkage	Inspect or Lubricate	I/L	I/L	I/L	I/L	I/L
Spark Plugs	Inspect or Replace	ı		R	R	R
Electrical Equipment	Check Operation	С	С	С	С	С
Electrical Switches	Check Operation	С	С	С	С	С
Electrical Diagnostic Check	Digital Technician Computer			С	С	С
All EFI Vehicles Will Receive a Printout Using our Digital Technician Computer Verifying Proper Operation at 10K						
Engine Idle Speeds	Check and Adjustment	С	C	С	С	С
Front Fork Oil	Replace				R	
Steering Head Bearings -	Adjust and Lubricate	A/L		A/L	A/L	A/L
Rear Fork Bearings	Repack					R
Windshield Bushings	Inspect					I
Fuel Door and Saddlebags	Lubricate Hinges and Latches	L	L	L	L	L
Critical Fasteners	Check Tightness	С	C	C	C	С
Battery	Verify Charging and Connections	V	V	V	V	V
	Verify Operation of All Components					
Road Test	and System Functions	V	V	V	V	V
Wash	Hot & Soapy with Air Blow Dry	W	W	W	W	W

R = Replace

I = Inspect

A = Adjust

L = Lubricate

C = Clean

C = CleanX = Check

V = Verify

W = Wash

With Optional Oil and Filter-----

For Synthetic Lubricant - Add

Pre 2000- Inspect and Repack Wheel Bearings - Add